

# P 401/25-90K

Wheel with pneumatic tire, with pressed steel rim

EAN 4047526254872  
ID 254870  
Customs tariff number 87169090



## tire:

- pneumatic tire, ribbed profile, hardness 60 Shore A
- 2-ply rating, with inner tube
- maximum operational comfort
- excellent floor preservation, particularly quiet operation
- color black

## Rim:

- pressed steel
- with welded tubular steel hub
- lacquered, color silver

## Other features:

- chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +50 °C
- the wheel and tire dimensions provided here apply to new tires that are not bearing a load. Their width and diameter may change when they are in use.
- speeds up to 16 km/h possible for wheels with ball bearing and reduced load capacity

## Technical data:

Wheel Ø (D)	☞	400 mm
Wheel width	⌊	100 mm
Tyre dimensions		4.00-8
Ply rating	≡	2
Load capacity at 4 km/h	⚖	250 kg
Load capacity at 16 km/h	⚖	190 kg
Load capacity (static)	⚖	250 kg
Tyre pressure	🚗	2.0 / 30 bar / psi
Bearing type	⦿	ball bearing
Axle bore Ø (d)		25 mm
Hub keyway (T1)	⌘	90 mm
Profile	≡≡	ribbed profile
Temperature resistance min		-20 °C
Temperature resistance max		50 °C
Tread and tyre hardness		60 Shore A
Unit weight	⚖	3.2 kg
Non-marking	✗	
Non-staining	✗	
Antistatic	⚡	✗
ProductDetail.TechnicalData.Esd	✗	
Electrically conductive	⚡	✗
Corrosion-resistant	✗	
Heat-resistant	🔥	✗
Tread hydrolysis-resistant	✗	



## Tread and tyre hardness

■ ■ ■ ■ ■ 60 Shore A

## Rolling resistance

■ ■ ■ ■ ■ good

## Wear resistance

■ ■ ■ ■ ■ satisfactory

## Operating noise / floor surface preservation

■ ■ ■ ■ ■ excellent



