

BK-RD 100R-1

Pressed steel fixed caster, heavy duty design, with top plate fitting, wheel with "Blickle Comfort" two-component solid rubber tires, with pressed steel rim

EAN 4047526263096

ID 263095

Customs tariff number 87169090



rig: BK series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: RD series














- tire: two-component solid rubber "Blickle Comfort", hardness 65 Shore A, color black
- rim: pressed steel, strong rim structure with tubular steel hub, bolted or pressed, zinc-plated, blue-passivated, Cr6-free

Other features:

- chemical resistance to many aggressive substances, except oils
- operating temperature: -25 °C to +80 °C, reduced load capacity over +60 °C



Technical data:

Wheel Ø (D)		100 mm
Wheel width		30 mm
Load capacity at 4 km/h		100 kg
Load capacity (static)		250 kg
Bearing type		roller bearing
Total height (H)		130 mm
Plate size		100 x 85 mm
Bolt hole spacing		80 x 60 mm
Bolt hole Ø		9 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight		0.8 kg
Non-marking		×
Non-staining		×
Antistatic		×
Electrically conductive		×
Corrosion-resistant		×
Heat-resistant		×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×

Tread and tyre hardness

 65 Shore A

Rolling resistance


 good

Wear resistance

 satisfactory

Operating noise / floor surface preservation

 very good



Product references



Corresponding swivel caster LK-RD 100R-1



Wheel used RD 100/15R