

## BKRA-VPA 80G

Light duty fixed caster, with bolt hole, wheel with solid rubber tires, with synthetic rim

EAN 4047526310851

ID 310854

Customs tariff number 83022000



**rig:** BKRA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free













**Wheel:** VPA series

- tire: high-quality solid rubber, hardness 80 Shore A, color gray, non-marking, non-staining
- rim: high-quality nylon 6 or polypropylene in the electrically conductive version "-EL", impact resistant, color black

**Other features:**

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C

### Technical data:

Wheel Ø (D)		80 mm
Wheel width		25 mm
Load capacity at 3 km/h		80 kg
Load capacity (static)		200 kg
Bearing type		plain bore
Total height (H)		108 mm
Plate Ø		57 mm
Bolt hole		13 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		80 Shore A
Unit weight		0.3 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



### Tread and tyre hardness

 80 Shore A

### Rolling resistance


 good

### Wear resistance

 sufficient

### Operating noise / floor surface preservation

 very good



## Product references



**Corresponding swivel caster LKRA-VPA 80G**



**Wheel used VPA 80/12G**