

LRA-VPA 50K-FI-E03

Light duty swivel caster, with bolt hole fitting, with metal expander, with brake system 'stop-fix', wheel with solid rubber tires, with synthetic rim

EAN 4047526315306

ID 315309

Customs tariff number 83022000



rig: LRA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: VPA series

- tire: high-quality solid rubber, hardness 80 Shore A, color gray, non-marking, non-staining
- rim: high-quality nylon 6 or polypropylene in the electrically conductive version "-EL", impact resistant, color black

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C

Technical data:

Wheel Ø (D)	☉	50 mm
Wheel width	⊥	18 mm
Load capacity at 3 km/h	⚖	40 kg
Load capacity (static)	⚖	100 kg
Bearing type	☉	ball bearing
Total height (H)	⊕	72 mm
Internal tube dimension	☉	25–30 mm
ProductDetail.TechnicalData.InnerPipeDimensionSquareTube		21–25 mm
Offset (F)	⊕	24 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		80 Shore A
Unit weight	⚖	0.4 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×



Tread and tyre hardness

■ ■ ■ ■ □ 80 Shore A

Rolling resistance



■ ■ ■ ■ □ good

Wear resistance

■ □ □ □ □ sufficient

Operating noise / floor surface preservation

■ ■ ■ ■ □ very good



Product references



Corresponding rigid caster BRA-VPA 50K



Corresponding swivel caster LRA-VPA 50K-E03



Wheel used VPA 50/6K