Product Data Sheet

Blickle

V 162/20G

Wheel with standard solid rubber tire, with pressed steel rim, reinforced design

EAN 4047526040994 ID 40998 Customs tariff number 87169090



tire:

- standard solid rubber, hardness 80 Shore A
- · very good operational comfort
- very good floor preservation, low-noise operation
- · color black

Rim:

- · pressed steel
- strong rim structure with tubular steel hub, bolted or pressed
- zinc-plated, blue-passivated, Cr6-free

Other features:


- chemical resistance to many aggressive substances, except oils
- operating temperature: -25 °C to +80 °C, reduced load capacity over +60 °C

Technical data:

Wheel Ø (D)	0	160 mm
Wheel width	,D,	40 mm
Load capacity at 4 km/h	ä	135 kg
Load capacity (static)	凸	340 kg
Bearing type	•	plain bore
Axle bore Ø (d)		20 mm
Hub keyway (T1)	-0-	60 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		80 Shore A
Unit weight	G	1.2 kg
Non-marking		×
Non-staining		×
Antistatic	(7)	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	7	×
Corrosion-resistant		×
Heat-resistant	F	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×







19.05.2024 | www.blickle.ca 1/1