

FTH 30x8/6-6K

Guide roller with Blickle Extrathane® polyurethane tread

EAN 4047526463717

ID 463711

Customs tariff number 83022000



Tread:

- high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A
- low rolling resistance
- high abrasion resistance
- high cut and tear propagation resistance
- color light brown, non-marking, non-staining
- tread cast directly onto the ball bearing
- excellent chemical connection

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -5 °F to +160 °F, temporarily up to +195 °F, reduced load capacity over +105 °F
- load capacity specifications refer to obstacle-free applications



Technical data:

Wheel Ø (D)	☉	30 mm
Wheel width	⊥	8 mm
Load capacity at 4 km/h	⚖	25 kg
Load capacity (static)	⚖	65 kg
Bearing type	⊙	ball bearing
Ball bearing		626 2RS
Axle bore Ø (d)		6 mm
Clamping length (T5)	⚙	6 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		92 Shore A
Unit weight	⚖	0.1 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×

Tread and tyre hardness

■ ■ ■ ■ ■ □ 92 Shore A

Rolling resistance

■ ■ ■ ■ ■ □ very good

Wear resistance

■ ■ ■ ■ ■ □ very good

Operating noise / floor surface preservation

■ ■ ■ ■ □ □ good

