

LH-SPO 125G-1-FA

Pressed steel swivel caster, heavy duty design, with top plate fitting, nylon heavy duty wheel, with steel thread guard

EAN 4047526023836

ID 488569

Customs tariff number 87169090



rig: LH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to **four specially-shaped, hardened bearing seats**

Wheel: SPO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, extremely robust heavy-duty version, color natural white

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

Technical data:

Wheel Ø (D)	☉	125 mm
Wheel width	⊥	40 mm
Load capacity at 4 km/h	⬆	700 kg
Load capacity (static)	⬆	1,750 kg
Bearing type	☉	plain bore
Total height (H)	⌀	165 mm
Plate size	⌘	100 x 85 mm
Bolt hole spacing	⌘	80 x 60 mm
Bolt hole Ø	⌀	9 mm
Offset (F)	⌀	45 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		70 Shore D
Unit weight	⚖	1.7 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	✗
Electrically conductive	⚡	✗
Corrosion-resistant		✗
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



Tread and tyre hardness

■■■■■ 70 Shore D

Rolling resistance



■■■■■ excellent

Wear resistance

■■■■■ good

Operating noise / floor surface preservation

■■■■■ satisfactory



Product references



Corresponding standard locking LH-SP0 125G-1-FI-FA



Corresponding rigid caster BH-SP0 125G-1-FA



Wheel used SP0 125/15G