

## LKRA-VPA 125K-11-E17

**Light duty swivel caster with bolt hole fitting, with metal expander, wheel with solid rubber tires, with synthetic rim**

**EAN** 4047526616243

**ID** 616243

**Customs tariff number** 83022000



**rig:** LKRA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** VPA series

- tire: high-quality solid rubber, hardness 80 Shore A, color gray, non-marking, non-staining
- rim: high-quality nylon 6 or polypropylene in the electrically conductive version "-EL", impact resistant, color black

**Other features:**

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C

**Technical data:**

Wheel Ø (D)	☉	125 mm
Wheel width	⊥	25 mm
Load capacity at 3 km/h	⚖	100 kg
Load capacity (static)	⚖	250 kg
Bearing type	⊙	ball bearing
Total height (H)	⊕	161 mm
Internal tube dimension	👁	39–45 mm
Offset (F)	⌘	40 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		80 Shore A
Unit weight	⚖	0.9 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×



**Tread and tyre hardness**

■ ■ ■ ■ □ 80 Shore A

**Rolling resistance**



■ ■ ■ ■ □ good

**Wear resistance**

■ □ □ □ □ sufficient

**Operating noise / floor surface preservation**

■ ■ ■ ■ □ very good



## Product references



**Corresponding standard locking LKRA-VPA 125K-11-FI-E17**



**Wheel used VPA 125/8K**