

BO-ALEV 200K-SG

Heavy duty welded steel fixed caster, heavy duty wheel with "Blickle EasyRoll" elastic solid rubber tires, with aluminum wheel center, non-marking, gray

EAN 4047526654221

ID 654228

Customs tariff number 87169090



rig: BO series

- solid welded steel construction, zinc-plated, blue-passivated, Cr6-free

Wheel: ALEV series














- tire: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, color gray, non-marking
- wheel center: die-cast aluminium

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +140 °F



Technical data:

Wheel Ø (D)		200 mm
Wheel width		50 mm
Load capacity at 4 km/h		500 kg
Load capacity (static)		1,250 kg
Bearing type		ball bearing
Total height (H)		245 mm
Plate size		140 x 110 mm
Bolt hole spacing		105 x 75–80 mm
Bolt hole Ø		11 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight		3.6 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tyre hardness

 65 Shore A

Rolling resistance


 very good

Wear resistance

 good

Operating noise / floor surface preservation

 very good



Product references



Corresponding swivel caster LO-ALEV 200K-SG



Wheel used ALEV 200/20K-SG