LK-POEV 125KA-3-FI-SB

Pressed steel swivel caster, heavy duty design, with brake system 'stopfix', heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with nylon wheel center, non-marking, blue, with synthetic thr ead quard, small

EAN 4047526682132 ID 682138 Customs tariff number 87169090

Made in Germany

rig: LK series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin (from wheel Ø 125x50 mm)
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: POEV series

- tire: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, color blue, non-marking
- wheel center: high-quality nylon 6, impact resistant, color black

Other features:

- with synthetic thread guard, small
- · high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F


Technical data:


Wheel @ (D)	\odot	125 mm
Wheel Ø (D)	v	125 mm
Wheel width	, [],	37 mm
Load capacity at 4 km/h	රි	250 kg
Load capacity (static)	රි	625 kg
Bearing type	۲	ball bearing (C)
Total height (H)	ġ	155 mm
Plate size		140 x 110 mm
Bolt hole spacing	Ċ;	105 x 75–80 mm
Bolt hole Ø	4	11 mm
Offset (F)	ø	46 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		65 Shore A
Unit weight	ð	1.5 kg
Non-marking		1
Non-staining		✓
Antistatic	(4)	×
Electrically conductive	(1)	×
Corrosion-resistant		×
Heat-resistant	ß	×
Tread hydrolysis-resistant		×














Suitable for autoclaves	×
Suitable for machine washing	×

Product references



Corresponding rigid caster BK-POEV 125KA-3-SB



Corresponding swivel caster LK-POEV 125KA-3-SB

