

## TPA 200/20G

Wheel with thermoplastic rubber tread, with polypropylene wheel center

EAN 4047526110901

ID 746947

Customs tariff number 87169090



### Tread:

- high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A
- low rolling and swivel resistance
- color gray, non-marking
- chemically-bonded inseparable connection with the wheel center

### Wheel center:

- high-quality polypropylene, impact resistant
- color silver gray

### Other features:

- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C
- tread contains oil, may stain sensitive surfaces. alternatives: series VPA, VPP, POES, POEV, PATH

### Technical data:

Wheel Ø (D)	☉	200 mm
Wheel width	⌈⌋	40 mm
Load capacity at 4 km/h	⚖	250 kg
Load capacity (static)	⚖	625 kg
Bearing type	☉	plain bore
Axle bore Ø (d)		20 mm
Hub keyway (T1)	⌈⌋	60 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		85 Shore A
Unit weight	⚖	0.5 kg
Non-marking		✓
Non-staining		✗
Antistatic	⚡	✗
ProductDetail.TechnicalData.Esd		✗
Electrically conductive	⚡	✗
Corrosion-resistant		✓
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗



### Tread and tyre hardness

■ ■ ■ ■ □ □ 85 Shore A

### Rolling resistance

■ ■ ■ ■ □ very good

### Wear resistance

■ ■ □ □ □ satisfactory

### Operating noise / floor surface preservation

■ ■ ■ □ □ good

