

BH-POEV 125K-3-SB

Pressed steel fixed caster, heavy duty design, with top plate fitting, heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with nylon wheel center, non-marking, blue

EAN 4047526002763

ID 749147

Customs tariff number 87169090



rig: BH series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate

Wheel: POEV series

- tire: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, color blue, non-marking
- wheel center: high-quality nylon 6, impact resistant, color black

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F



Technical data:

Wheel Ø (D)	⌀	125 mm
Wheel width	⊥	37 mm
Load capacity at 4 km/h	⬆	250 kg
Load capacity (static)	⬆	625 kg
Bearing type	⊙	ball bearing
Total height (H)	⊘	165 mm
Plate size	⊞	140 x 110 mm
Bolt hole spacing	⊞	105 x 75–80 mm
Bolt hole Ø	⌀	11 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight	⚖	1.5 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×

Tread and tyre hardness

65 Shore A

Rolling resistance


very good

Wear resistance

good

Operating noise / floor surface preservation

very good



Product references



Corresponding swivel caster LH-POEV 125K-3-SB



Wheel used POEV 125/15K-SB