Blickle

L-VW 202R-ST-FA

Pressed steel swivel caster, medium duty design, with top plate fitting, with brake system 'stop-top', wheel with "Blickle Soft" soft rubber tire, with pressed steel rim, with steel thread quard

EAN 4047526013288 ID 749558 Customs tariff number 87169090



rig: L series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- · double ball bearing in the swivel head
- strong central kingpin (from wheel Ø 150 mm)
- · swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: VW series

- tire: soft rubber "Blickle Soft", hardness 50 Shore A, color black (wheel Ø 260 mm with additional hard rubber core)
- rim: pressed steel, strong rim structure with tubular steel hub, bolted or pressed, zinc-plated, blue-passivated, Cr6-free

Other features:


- chemical resistance to many aggressive substances, except oils
- operating temperature: -25 °C to +80 °C, reduced load capacity over +60 °C
- puncture-proof alternatives for pneumatic tires


Technical data:


Wheel Ø (D)	0	200 mm
Wheel width	, 0,	50 mm
Load capacity at 4 km/h	පි	100 kg
Load capacity (static)	凸	250 kg
Bearing type	•	roller bearing
Profile	::	round profile
Total height (H)	Q	235 mm
Plate size		140 x 110 mm
Bolt hole spacing	Ď:	105 x 75–80 mm
Bolt hole Ø	4	11 mm
Offset (F)	Ø	63 mm
Temperature resistance min		-25 °C
Temperature resistance max		70 °C
Tread and tyre hardness		50 Shore A
Unit weight	Ø	4.1 kg
Non-marking		×
Non-staining		×
Antistatic	7	×
Electrically conductive	(7)	×
Corrosion-resistant		×
Heat-resistant	E	×
Tread hydrolysis-resistant		×











26.05.2024 | www.blickle.ca 1/2

Suitable for autoclaves	×
Suitable for machine washing	×

Product references







26.05.2024 | www.blickle.ca 2/2