

LK-SPO 150G-FI-FA

Pressed steel swivel caster, heavy duty design, with brake system 'stop-fix', nylon heavy duty wheel, with steel thread guard

EAN 4047526030087

ID 750527

Customs tariff number 87169090



rig: LK series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin (from wheel Ø 125x50 mm)
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: SPO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, extremely robust heavy-duty version, color natural white

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

Technical data:

Wheel Ø (D)	☉	150 mm
Wheel width	⏏	50 mm
Load capacity at 4 km/h	⚖	600 kg
Load capacity (static)	⚖	1,500 kg
Bearing type	⦿	plain bore
Total height (H)	⌀	197 mm
Plate size	📏	140 x 110 mm
Bolt hole spacing	📏	105 x 75–80 mm
Bolt hole Ø	🔧	11 mm
Offset (F)	📏	53 mm
Temperature resistance min		-25 °C
Temperature resistance max		70 °C
Tread and tyre hardness		70 Shore D
Unit weight	⚖	3.2 kg
Non-marking		✓
Non-staining		✓
Antistatic	🔧	✗
Electrically conductive	🔧	✗
Corrosion-resistant		✗
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



Tread and tyre hardness

■■■■■ 70 Shore D

Rolling resistance



■■■■■ excellent

Wear resistance

■■■■■ good

Operating noise / floor surface preservation

■■■■■ satisfactory



Product references



Corresponding rigid caster BH-SP0 150G-FA



Corresponding swivel caster LK-SP0 150G-FA



Wheel used SP0 150/20G