

V 302/30-55G

Wheel with standard solid rubber tire, with pressed steel rim, reinforced design

EAN 4047526066413

ID 752206

Customs tariff number 87169090



tire:

- standard solid rubber, hardness 80 Shore A
- very good operational comfort
- very good floor preservation, low-noise operation
- color black

Rim:

- pressed steel
- strong rim structure with tubular steel hub, bolted or pressed
- zinc-plated, blue-passivated, Cr6-free

Other features:

- chemical resistance to many aggressive substances, except oils
- operating temperature: -25 °C to +80 °C, reduced load capacity over +60 °C
- Support load

Technical data:

Wheel Ø (D)	☞	300 mm
Wheel width	⌈	60 mm
Load capacity at 4 km/h	⚖	700 kg
Load capacity (static)	⚖	1,750 kg
Bearing type	⊙	plain bore
Axle bore Ø (d)		30 mm
Hub keyway (T1)	⋈	55 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		80 Shore A
Unit weight	⚖	4.2 kg
Non-marking		×
Non-staining		×
Antistatic	⚡	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×



Tread and tyre hardness

■ ■ ■ □ □ 80 Shore A

Rolling resistance

■ ■ □ □ □ satisfactory

Wear resistance

■ □ □ □ □ sufficient

Operating noise / floor surface preservation

■ ■ ■ ■ □ very good

