

ALBS 300/25K

Heavy duty wheel, with Blickle Besthane® Soft polyurethane tread, with aluminum wheel center

EAN 4047526111533

ID 752956

Customs tariff number 87169090



Tread:

- high-quality polyurethane elastomer Blickle Besthane® Soft, hardness 75 Shore A
- extra-thick elastic tread for excellent operational comfort
- very good floor preservation, low-noise operation
- very low rolling resistance
- **high dynamic load capacity**
- high abrasion resistance
- high cut and tear propagation resistance
- color blue, non-marking, non-staining
- excellent chemical connection with the wheel center

Wheel center:

- die-cast aluminium

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -5 °F to +160 °F, temporarily up to +195 °F, reduced load capacity over +105 °F

Technical data:

Wheel Ø (D)	☉	300 mm
Wheel width	⌈	60 mm
Load capacity at 4 km/h	⊞	1,150 kg
Load capacity at 6 km/h	⊞	800 kg
Load capacity at 10 km/h	⊞	570 kg
Load capacity at 16 km/h	⊞	460 kg
Load capacity (static)	⊞	2,875 kg
Bearing type	☉	ball bearing
Axle bore Ø (d)		25 mm
Hub keyway (T1)	⌈	70 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		75 Shore A
Unit weight	⊞	3.5 kg
Non-marking		✓
Non-staining		✓
Antistatic	⌈	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	⌈	×
Corrosion-resistant		×
Heat-resistant	⌈	×
Tread hydrolysis-resistant		✓
Suitable for autoclaves		×



Tread and tyre hardness

■ ■ ■ ■ □ □ 75 Shore A

Rolling resistance

■ ■ ■ ■ ■ ■ excellent

Wear resistance

■ ■ ■ ■ ■ □ very good

Operating noise / floor surface preservation

■ ■ ■ ■ ■ □ very good

