Product Data Sheet

BS-SVS 300K

Heavy duty welded steel fixed caster, extra heavy duty solid steel wheel

EAN 4047526112608 ID 754244 Customs tariff number 87169090



rig: BS series

- particularly robust welded steel construction
- zinc-plated, yellow-passivated, Cr6-free

Wheel: SVS series

• heat-treatable steel, hardness 190-230 HB, slightly crowned tread


Other features:

- chemical resistance to many aggressive substances
- operating temperature: -20 °C to +120 °C
- · consider the surface pressure on sensitive floors due to high point loads


Technical data:

| Wheel Ø (D) | Ø | 300 mm |
|------------------------------|-----|--------------|
| Wheel width | "O. | 90 mm |
| Load capacity at 4 km/h | රි | 12,000 kg |
| Load capacity (static) | රි | 30,000 kg |
| Bearing type | ۲ | ball bearing |
| Total height (H) | ଜ୍ | 430 mm |
| Plate size | | 400 x 300 mm |
| Bolt hole spacing | t; | 340 x 240 mm |
| Bolt hole Ø | 쎽 | 26 mm |
| Temperature resistance min | | -20 °C |
| Temperature resistance max | | 120 °C |
| Tread and tyre hardness | | 190–230 HB |
| Unit weight | ම | 87.7 kg |
| Non-marking | | ✓ |
| Non-staining | | ✓ |
| Antistatic | (†) | × |
| Electrically conductive | (†) | ✓ |
| Corrosion-resistant | | × |
| Heat-resistant |), | × |
| Tread hydrolysis-resistant | | × |
| Suitable for autoclaves | | × |
| Suitable for machine washing | | × |

| Tread and tyre hardness 190–230 HB |
|--|
| Rolling resistance excellent |
| Wear resistance excellent |
| Operating noise / floor surface preservation |



Product references







Corresponding swivel caster LS-SVS 300K

Wheel used SVS 300/100K