

## B-RD 252R-VLI-FA

Pressed steel fixed caster, medium duty design, with top plate fitting, wheel with "Blickle Comfort" two-component solid rubber tires, with pressed steel rim, non-marking, gray, with steel thread guard

EAN 4047526158958

ID 850012

Customs tariff number 87169090



**rig:** B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Wheel:** RD series














- tire: two-component solid rubber "Blickle Comfort", hardness 56 Shore A, color gray
- rim: pressed steel, strong rim structure with tubular steel hub, bolted or pressed, zinc-plated, blue-passivated, Cr6-free

**Other features:**

- chemical resistance to many aggressive substances, except oils
- operating temperature: -25 °C to +80 °C, reduced load capacity over +60 °C



### Technical data:

Wheel Ø (D)		250 mm
Wheel width		60 mm
Load capacity at 4 km/h		450 kg
Load capacity (static)		1,125 kg
Bearing type		roller bearing
Total height (H)		295 mm
Plate size		220 x 130 mm
Bolt hole spacing		190 x 75 mm
Bolt hole Ø		15 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		56 Shore A
Unit weight		6.1 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

#### Tread and tyre hardness

 56 Shore A

#### Rolling resistance


 good

#### Wear resistance

 satisfactory

#### Operating noise / floor surface preservation

 very good



## Product references



**Corresponding swivel caster L-RD 252R-VLI-FA**



**Wheel used RD 252/25R-VLI**