

LH-POEV 200XR-CS13-SB

Pressed steel swivel caster, heavy duty design, with top plate fitting, with central brake system 'central-stop', heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with nylon wheel center, non-marking, blue

EAN 4047526185138

ID 851874

Customs tariff number 87169090



rig: LH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to **four specially-shaped, hardened bearing seats**

Wheel: POEV series

- tire: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, color blue, non-marking
- wheel center: high-quality nylon 6, impact resistant, color black

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -15 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F

Technical data:

Wheel Ø (D)	☞	200 mm
Wheel width	⊥	50 mm
Load capacity at 4 km/h	⬇	500 kg
Load capacity (static)	⬇	1,250 kg
Bearing type	⦿	roller bearing
Total height (H)	⌀	245 mm
Plate size	⊞	140 x 110 mm
Bolt hole spacing	⊞	105 x 75–80 mm
Bolt hole Ø	⌀	11 mm
Offset (F)	⌀	67 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight	⚖	3.9 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×



Tread and tyre hardness

■■■■■ 65 Shore A

Rolling resistance



■■■■■ very good

Wear resistance

■■■■■ good

Operating noise / floor surface preservation

■■■■■ very good



Product references



Corresponding rigid caster BH-POEV 200XR-SB



Corresponding swivel caster LH-POEV 200XR-SB



Wheel used POEV 200/20XR-SB