

BK-PO 75XR-FA

Pressed steel fixed caster, heavy duty design, with top plate fitting, nylon wheel, with steel thread guard

EAN 4047526196257

ID 852723

Customs tariff number 87169090



rig: BK series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: PO series














- high-quality nylon 6, impact resistant, hardness 70 Shore D, color natural white

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C



Technical data:

Wheel Ø (D)		75 mm
Wheel width		32 mm
Load capacity at 4 km/h		200 kg
Load capacity (static)		500 kg
Bearing type		roller bearing
Total height (H)		108 mm
Plate size		100 x 85 mm
Bolt hole spacing		80 x 60 mm
Bolt hole Ø		9 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		70 Shore D
Unit weight		0.5 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tyre hardness

 70 Shore D

Rolling resistance


 excellent

Wear resistance

 good

Operating noise / floor surface preservation

 satisfactory



Product references



Corresponding swivel caster LK-PO 75XR-FA



Wheel used PO 75/12XR