

## LH-SPO 200K-CS13-FA

**Pressed steel swivel caster, heavy duty design, with top plate fitting, with central brake system 'central-stop', nylon heavy duty wheel, with steel thread guard**

**EAN** 4047526199005

**ID** 852929

**Customs tariff number** 87169090



**rig:** LH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to **four specially-shaped, hardened bearing seats**

**Wheel:** SPO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, extremely robust heavy-duty version, color natural white

**Other features:**

- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +80 °C, reduced load capacity over +35 °C
- Extra heavy-duty wheel design

**Technical data:**

Wheel Ø (D)	☉	200 mm
Wheel width	⊥	50 mm
Load capacity at 4 km/h	⚖	900 kg
Load capacity (static)	⚖	2,250 kg
Bearing type	⊙	ball bearing
Total height (H)	⊕	245 mm
Plate size	☐	140 x 110 mm
Bolt hole spacing	☐	105 x 75–80 mm
Bolt hole Ø	⌀	11 mm
Offset (F)	⊕	67 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tyre hardness		70 Shore D
Unit weight	⚖	4.5 kg
Non-marking		✓
Non-staining		✓
Antistatic	⚡	✗
Electrically conductive	⚡	✗
Corrosion-resistant		✗
Heat-resistant	🔥	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



**Tread and tyre hardness**

■■■■■ 70 Shore D

**Rolling resistance**



■■■■■ excellent

**Wear resistance**

■■■■□ good

**Operating noise / floor surface preservation**

■■■■□ satisfactory



## Product references



**Corresponding rigid caster BH-SP0 200K-FA**



**Corresponding swivel caster LH-SP0 200K-FA**



**Wheel used SPO 200/20K**