

POEV 80/8KFD-SB

Heavy duty wheel, with 'Blickle EasyRoll' elastic solid rubber tyres, with nylon wheel centre, non-marking, blue, with synthetic thread guard

EAN 4047526212193

ID 856394

Customs tariff number 87169090



tyre:

- high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A
- very good operational comfort
- very good floor preservation, low-noise operation
- low rolling resistance
- color blue, non-marking
- vulcanised onto the wheel center

Wheel center:

- high-quality nylon 6, impact resistant
- color black

Other features:

- large thread guard, with additional, ball bearing seals
- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F

Technical data:

Wheel Ø (D)	☉	80 mm
Wheel width	⊥	32 mm
Load capacity at 4 km/h	⚖	140 kg
Load capacity (static)	⚖	350 kg
Bearing type	⦿	ball bearing (C)
Axle bore Ø (d)		8 mm
Hub keyway (T1)	⋈	36 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight	⚖	0.2 kg
Non-marking	✓	
Non-staining	✓	
Antistatic	⚡	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×



Tread and tyre hardness

■ ■ ■ ■ ■ 65 Shore A

Rolling resistance

■ ■ ■ ■ ■ very good

Wear resistance

■ ■ ■ ■ ■ good

Operating noise / floor surface preservation

■ ■ ■ ■ ■ very good

