Blickle

POEV 100/10KAD

Heavy duty wheel, with 'Blickle EasyRoll' elastic solid rubber tyres, with nylon wheel centre, with synthetic thread guard

EAN 4047526212230 **ID** 856398 **Customs tariff number** 87169090



tire:

- high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A
- · very good operational comfort
- · very good floor preservation, low-noise operation
- low rolling resistance
- · color black
- · vulcanised onto the wheel center

Wheel center:

- · high-quality nylon 6, impact resistant
- · color black

Other features:

- small thread guard, with additional, ball bearing seal
- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F



Wheel Ø (D)	0	100 mm
Wheel width	.0.	32 mm
Load capacity at 4 km/h	S	200 kg
Load capacity (static)	凸	500 kg
Bearing type	•	ball bearing (C)
Axle bore Ø (d)		10 mm
Hub keyway (T1)	·()·	46 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight	適	0.3 kg
Non-marking		×
Non-staining		×
Antistatic	7	×
ProductDetail.TechnicalData.Esd		×
Electrically conductive	7	×
Corrosion-resistant		×
Heat-resistant	F	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×







