

POEV 125/15XR

Heavy duty wheel, with "Blickle EasyRoll" elastic solid rubber tires, with nylon wheel center

EAN 4047526089757

ID 89755

Customs tariff number 87169090



tire:

- high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A
- very good operational comfort
- very good floor preservation, low-noise operation
- low rolling resistance
- color black
- vulcanised onto the wheel center

Wheel center:

- high-quality nylon 6, impact resistant
- color black

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -15 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +95 °F



Technical data:

| | | |
|---------------------------------|----|----------------|
| Wheel Ø (D) | ☉ | 125 mm |
| Wheel width | ⌈⌋ | 37 mm |
| Load capacity at 4 km/h | ⚖ | 250 kg |
| Load capacity (static) | ⚖ | 625 kg |
| Bearing type | ⦿ | roller bearing |
| Axle bore Ø (d) | | 15 mm |
| Hub keyway (T1) | ⌘ | 45 mm |
| Temperature resistance min | | -25 °C |
| Temperature resistance max | | 80 °C |
| Tread and tyre hardness | | 65 Shore A |
| Unit weight | ⚖ | 0.3 kg |
| Non-marking | | × |
| Non-staining | | × |
| Antistatic | ⚡ | × |
| ProductDetail.TechnicalData.Esd | | × |
| Electrically conductive | ⚡ | × |
| Corrosion-resistant | | ✓ |
| Heat-resistant | 🔥 | × |
| Tread hydrolysis-resistant | | × |
| Suitable for autoclaves | | × |

Tread and tyre hardness

■ ■ ■ ■ ■ 65 Shore A

Rolling resistance

■ ■ ■ ■ ■ very good

Wear resistance

■ ■ ■ ■ ■ good

Operating noise / floor surface preservation

■ ■ ■ ■ ■ very good

