

BHF-ALEV 125K-14-SG

Pressed steel fixed caster, heavy duty design, with steel spring, heavy duty wheel with "Blickle EasyRoll" elastic solid rubber tires, with aluminum wheel center, non-marking, gray

EAN 4047526330637

ID 910053

Customs tariff number 87169090



Rig: BHF series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- robust spring structure with steel spring
- maintenance-free spring mechanism








Wheel: ALEV series

- tire: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, color gray, non-marking
- wheel center: die-cast aluminium

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -5 °F to +175 °F, temporarily up to +210 °F, reduced load capacity over +140 °F

Technical data:

Wheel Ø (D)		125 mm
Wheel width		40 mm
Load capacity at 4 km/h		250 kg
Load capacity (static)		600 kg
Bearing type		ball bearing
Spring tension		240 kg
Initial tension		30 kg
Spring travel		21 mm
Total height (H)		200 mm
Plate size		114.3 x 101.6 mm
Bolt hole spacing		66,68 x 92,1 / 76,2 x 76,2 mm
Bolt hole Ø		11 mm
Offset (F)		56 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight		3.4 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗



Tread and tyre hardness

 65 Shore A

Rolling resistance


 very good

Wear resistance

 good

Operating noise / floor surface preservation

 very good



Tread hydrolysis-resistant	×
Suitable for autoclaves	×
Suitable for machine washing	×

Product references



Corresponding swivel caster LHF-ALEV 125K-14-SG



Wheel used ALEV 125/15K-SG