

## BH-ALTH 202K

**Pressed steel fixed caster, heavy duty design, with top plate fitting, heavy duty wheel with Blickle Extrathane® polyurethane tread, with aluminum wheel center**

**EAN** 4047526357788

**ID** 936649

**Customs tariff number** 87169090



**rig:** BH series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate

**Wheel:** ALTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, color light brown, non-marking, non-staining
- wheel center: die-cast aluminium, color silver gray

**Other features:**

- high chemical resistance to many aggressive substances
- operating temperature: -5 °F to +160 °F, temporarily up to +195 °F, reduced load capacity over +105 °F
- With heavy-duty wheel center, reinforced design



**Technical data:**

Wheel Ø (D)	☉	200 mm
Wheel width	⊥	50 mm
Load capacity at 4 km/h	⬆	900 kg
Load capacity (static)	⬆	2,250 kg
Bearing type	☉	ball bearing
Total height (H)	⊕	245 mm
Plate size	☐	140 x 110 mm
Bolt hole spacing	⊕	105 x 75–80 mm
Bolt hole Ø	⊕	11 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		92 Shore A
Unit weight	⚖	3 kg
Non-marking	✓	
Non-staining	✓	
Antistatic	⚡	×
Electrically conductive	⚡	×
Corrosion-resistant		×
Heat-resistant	🔥	×
Tread hydrolysis-resistant		×
Suitable for autoclaves		×
Suitable for machine washing		×

**Tread and tyre hardness**

■■■■■□ 92 Shore A

**Rolling resistance**


■■■■■□ very good

**Wear resistance**

■■■■■□ excellent

**Operating noise / floor surface preservation**

■■■■■□ good



## Product references



**Corresponding swivel caster LUH-ALTH 202K**



**Wheel used ALTH 202/20K**