

L-PO 150G-ST-ELS

Pressed steel swivel caster, medium duty design, with top plate fitting, with brake system 'stop-top', nylon wheel, electrically conductive, Non-marking

EAN 4047526358839

ID 936912

Customs tariff number 87169090



rig: L series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin (from wheel Ø 150 mm)
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: PO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, color gray, non-marking

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C
- electrical conductivity (ohmic resistance) $\leq 10^4 \Omega$

Technical data:

Wheel Ø (D)	⌀	150 mm
Wheel width	⊥	50 mm
Load capacity at 4 km/h	⬆	400 kg
Load capacity (static)	⬆	1,000 kg
Bearing type	⊙	plain bore
Total height (H)	⊘	190 mm
Plate size	⊞	140 x 110 mm
Bolt hole spacing	⊞	105 x 75–80 mm
Bolt hole Ø	⌀	11 mm
Offset (F)	⊘	60 mm
Temperature resistance min		-25 °C
Temperature resistance max		70 °C
Tread and tyre hardness		70 Shore D
Unit weight	⬆	2.6 kg
Non-marking		✓
Non-staining		✓
Antistatic	⊞	✗
Electrically conductive	⊞	✓
Corrosion-resistant		✗
Heat-resistant	⊞	✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗



Tread and tyre hardness

■■■■■ 70 Shore D

Rolling resistance



■■■■■ excellent

Wear resistance

■■■■■ good

Operating noise / floor surface preservation

■■■■■ satisfactory



Product references



Corresponding rigid caster B-PO 150G-ELS



Corresponding swivel caster L-PO 150G-ELS



Wheel used PO 150/20G-ELS